

SHRINK TUNNEL STANDARD / LONG



KEY FEATURES

- Built-in Phase Reversal Protection to prevent motor damage and guarantee safety.
- Dedicated cooling fan system for long versions to ensure rapid, uniform wrap cooling.
- Heavy-duty build with energy-efficient heat management to reduce production costs.

TECHNICAL SPECIFICATIONS

Technical Data	QS4025STV QS4025STVL*	QS5040STVL	QS7545STVL
Window width (mm)	400	500	750
Window height (mm)	250	400	450
Chamber Length (mm)	1000	1000	1000
Voltage (V/Hz)	415/50/3 Phase	415/50/3 Phase	415/50/3 Phase
Power (W)	7500 / 9000*	12000	16500
Conveyor Length (mm)	1240 / 1790*	1790	1790
Machine Length (mm)	1260 / 1810*	1810	1810
Machine Width (mm)	670	770	1020
Machine Height (mm)	1455 (+50)**	1605 (+50)**	1655 (+50)**
Machine Weight (kg)	123 / 144*	157	200
Conveyor Speed (m/min)	0 – 7.2	0 – 7.2	0 – 7.2
Conveyor Height (mm)	790 (+50)**	790 (+50)**	790 (+50)**
Conveyor Rod Pitch (mm)	30	30	30

Note: * Represents specs for long version models (STVL). ** Height adjustments possible within range.



+91 82759 06362
+91 98901 94446



www.duggalheaters.com



duggalheater@gmail.com

Address: Shop no 4, Panacea Light, 753/754, Tapkir Galli, near Phadke Haud,
Phadke Haud, Budhwar Peth, Pune, Maharashtra 411002

ECONOMIC **SHRINK**
TUNNEL



BEST-SUITED USES

- POF/PVC shrink wrapping for cosmetics and retail packs
- Small-batch food container bundling & confectionery boxes
- Stationery, books, diaries, and promotional materials
- E-commerce parcel prep and protective product sealing

KEY FEATURES

- Optimized explicitly for POF and PVC shrink film applications.
- Adjustable chamber height to match diverse small-to-medium product profiles.
- Air flow deflector system for uniform, wrinkle-free sealing results.

TECHNICAL SPECIFICATIONS

Technical Parameter	Specification Details (QS4525DSTV)
Window width (mm)	450
Window height (mm)	250
Maximum packet size (LxWxH) (mm)	500x350x200
Maximum product weight (kg)	5
Machine dimensions (LxWxH) (mm)	1210x700x1080
Voltage frequency	415/50/3phase
Power (W)	7800
Conveyor length (mm)	1180
Conveyor speed (m/min)	0-20
Conveyor height (mm)	800
Conveyor rod pitch (mm)	30
Chamber length (mm)	900
Weight (kg)	123

**Designs are subject to continuous technical updates to optimize power usage and wrap quality.*



+91 82759 06362
+91 98901 94446



www.duggalheaters.com



duggalheater@gmail.com

Address: Shop no 4, Panacea Light, 753/754, Tapkir Galli, near Phadke Haud,
Phadke Haud, Budhwar Peth, Pune, Maharashtra 411002